



Assortment of main safety valves



MACHINERY Sp. z o.o.

Name	Analog	DN, mm	PN, Mpa	t° C	Media	L, mm	H, mm	Weight, kg
PV2.1.1.1-125/250-25	875-125-0	125/250	25	545	steam	380	1690	640
PV2.4.1.1-150/150-9,8	1202-150/150-0	150/150	9,8	540	steam	560	1160	415
PV1.4.1.1-150/150-9,8-01	530-150/150-0B	150/150	9,8	540	steam	560	1260	424
PV2.1.1.1-150/200-13,7	392-175/95-0r	150/200	13,7	560	steam	310	1350	446
PV2.1.1.1-150/200-9,8	392-175/95-0r-01	150/200	9,8	540	steam	310	1350	446
PV2.4.1.1-150/200-13,7-01	1203-150/200-0	150/200	13,7	560	steam	280	900	345
PV2.4.1.1-150/200-9,8	1203-150/200-0	150/200	9,8	540	steam	280	900	345
PV2.4.1.1-150/200-3,4	1203-150/200-0-01	150/200	3,4	300	steam	280	900	345
PV2.4.1.1-150/200-7,75	1203-150/200-0-02	150/200	7,75	521	steam	280	900	345
PV2.4.1.1-150/200-5,5	1203-150/200-0-03	150/200	5,5	488	steam	280	900	345
PV2.4.1.1-150/200-9,1	1203-150/200-0-04	150/200	9,1	540	steam	280	900	345
PV2.4.1.1-150/200-13,7	1203-150/200-0-07	150/200	13,7	560	steam	280	900	345
PV2.4.1.1-150/200-5,4	1203-150/200-0-13	150/200	5,4	545	steam	280	900	345
PV2.4.1.1-200/250-25	1029-200/250-0	200/250	25	545	steam	850	2090	1747
PV2.4.1.1-250/400-0,8-1,2	111-250/400-06	250/400	0,8-1,2	450	steam	760	860	756
PV2.4.1.1-250/400-1,3-4,1	111-250/400-06-01	250/400	1,3-4,1	450	steam	760	1200	767
PV2.4.1.1-250/400-4	694-250/400-06	250/400	4	545	steam	760	1200	767